



## DRUM PUMP P200

Designed specifically for pumping high viscosity sealants, adhesives and greases directly from standard open topped 200 litres size drums this robust pump is available with a choice of pressure ratios: 48:1, 56:1 or 75:1.

Suitable for use both as a central supply pump or for feeding application guns, dispensing valves or metering valves directly.

Pairs of pumps can be connected together to provide a running/standby facility, to ensure continuous, uninterrupted production.



### FEATURES AND BENEFITS

- Fits all standard 200 litre size drums
- Low level alarm/cut-off is standard
- Twin post ram design ensures positive priming with viscous materials
- High air/fluid pressure ratios handle materials up to 5,0 Mio. mpa s
- Seals resistant to chemical corrosion
- Hard chromed piston rods
- Adjustable packings
- Two hand safety operation is standard
- Simple and reliable operation
- Easily transported by lift truck



TECHNICAL DATA	
Maximum viscosity	up to 5 Mio. mPa s
Pressure ratio	22 / 48 / 56 or 75 : 1
Flow rate (per double stroke)	30 / 150 / 300 cc
Maximum stroke rate (double stroke)	20
Working pressure	20 - 250 bar
Maximum working pressure	400
Compressed air connection	1/2" BSP
Pumping output connection	1/2" / 1" / 1 1/4" BSP
Maximum air consumption	220 - 900 l/min
Maximum air inlet pressure	6 bar
Maximum container height	880 mm
Container-Æ	275 - 575 mm
Pump height on start-up in drum	1650 mm
Pump height extended	2600 mm
Base plate dimensions	900 x 600 mm
Weight	205 - 250 kg

### ACCESSORIES



Metering Valves



Fluid Pressure Regulators



Dispensing Valves

EQUIPMENT			
Forkliftable base plate	s	Follower plate	o
Portable	o	Cover plate	o
Pre-level alarm	s	Stainless steel wetted parts	o
Low level alarm with automatic shut-off			
Pneumatic FRL	s	Plasma coated wetted parts	o
Drum centring device	s	Drum-roll-in	o
Two hand safety operation	s	Pump with external valves	o

s = standard, o = optional



**Hilger u. Kern / Dopag Metering Technology**

Hilger u. Kern GmbH · Käfertaler Strasse 253 · 68167 Mannheim · GERMANY  
 Tel. +49 (0)621 37 05 0 · Fax +49 (0)621 37 05 271 · E-Mail: dosiertechnik@hilger-kern.de · Internet: www.hilger-kern.com  
 DOPAG Dosiertechnik und Pneumatik AG · Langackerstrasse 25 · 6330 Cham Switzerland  
 Tel. +41 (0)41 785 57 57 · Fax +41 (0)41 785 57 00 · E-Mail: info@dopag.ch · Internet: www.dopag.com